90 Degree Zinc Die Cast Connector, 2"

Part no. 8728 UPC 658746887289



Family image shown; colour and finish may differ.

cULus Listed | E197675 | Liquid-tight | metallic & non-metallic conduit


A 2-inch 90° zinc die-cast liquid-tight connector - terminates metallic or non-metallic Type B liquid-tight flexible conduit into a box or enclosure, with a sealing gland and gasket.

TRADE SIZE	2"
TYPE	90° connector
FOR	Metallic (LFMC) and non-metallic Type B liquid-tight conduit
MATERIAL	Zinc die-cast
LISTING	cULus Listed, file E197675
PACK	10 per carton

Specifications

Part number	8728
UPC / GTIN-12	658746887289
Trade size	2"
Listing	cULus Listed, file E197675
Material	Zinc die-cast
A - overall height	4.21 in
B - overall reach	5.06 in
C - thread length	0.71 in
Carton quantity	10
Catalog	Sealproof catalog, p. 37
Country of origin	USA - Elizabeth, New Jersey

DIMENSIONAL DRAWING



A overall height | B overall reach | C thread length. Nominal, in inches.

Features

- Available 3/8" through 4"
- For use with both Metallic Liquid Tight Conduit and Nonmetalic Liquid Tight Type B
- Zinc construction resists salt water, weak acids, gasoline, alcohol, oil, grease, & common solvents
- Resistant to outdoor weather conditions

DOCUMENTS
Part page: https://superflex.com/product/90-degree-zinc-die-cast-connector-2/
Sealproof Weatherproof catalog, Rev. 2026, p. 37: https://superflex.com/wp-content/uploads/2026/11/Sealproof-Weatherproof-Catalog
UL file E197675: https://iq.ulprospector.com/en/search?term=E197675