

Flexible Liquid Tight Conduit, 1/2", 1000 ft

Part no. 8431-R-1000 UPC 658746843117



Family image shown; colour and finish may differ.

UL Listed | E129973 | CSA Certified

Liquid-tight | Type B (LFNC-B)


1/2-inch flexible non-metallic liquid-tight conduit (Type B, LFNC-B), 1000 ft reel - a PVC raceway that keeps oil, water and sunlight off the conductors inside. Terminate it with Sealproof liquid-tight connectors.

TRADE SIZE	1/2"
LENGTH	1000 ft reel
COLOUR	Gray
MATERIAL	Flexible PVC
LISTING	UL Listed, file E129973; CSA Certified Type B (LFNC-B)
TEMPERATURE RATING	80°C dry / 60°C wet / 70°C oil resistant (105°C dry or 90°C wet available on request)

Specifications

Part number	8431-R-1000
UPC / GTIN-12	658746843117
I.D. / trade size	1/2"
Length	1000 ft
Colour / finish	Gray
Listing	UL Listed, file E129973; CSA Certified
Material	Flexible PVC
O.D.	0.820 - 0.840 in
I.D.	0.622 - 0.642 in
Min. bend radius	4 in
Temperature rating	80°C dry / 60°C wet / 70°C oil resistant (105°C dry or 90°C wet available on request)
Standard put-up	1000 ft per reel
Country of origin	USA - Elizabeth, New Jersey

DIMENSIONAL DRAWING



O.D. outside diameter | I.D. inside diameter | R minimum bend radius to the centreline. Nominal, in inches.

DOCUMENTS

Part page: <https://superflex.com/product/flexible-liquid-tight-conduit-1-2-1000-ft/>

Sealproof catalog, Rev. 2026 (PDF): <https://superflex.com/wp-content/uploads/2026/09/Sealproof-Weatherproof-Catalog-Rev-2026.pdf>

UL file E129973: <https://iq.ulprospector.com/en/search?term=E129973>