

Flexible Liquid Tight Conduit, 3/4", 700 ft

Part no. 8432-R-700 UPC 658746843391



Family image shown; colour and finish may differ.

Liquid-tight | Type B (LFNC-B)


Flexible flexible non-metallic liquid-tight conduit (Type B, LFNC-B), 700 ft reel - a PVC raceway that keeps oil, water and sunlight off the conductors inside. Terminate it with Sealproof liquid-tight connectors.

LENGTH	700 ft reel
COLOUR	Gray
MATERIAL	Flexible PVC
TEMPERATURE RATING	80°C dry / 60°C wet / 70°C oil resistant (105°C dry or 90°C wet available on request)

Specifications

Part number	8432-R-700
UPC / GTIN-12	658746843391
Length	700 ft
Material	Flexible PVC
O.D.	1.030 - 1.050 in
I.D.	0.820 - 0.840 in
Min. bend radius	5 in
Temperature rating	80°C dry / 60°C wet / 70°C oil resistant (105°C dry or 90°C wet available on request)
Standard put-up	700 ft per reel
Country of origin	USA - Elizabeth, New Jersey

DIMENSIONAL DRAWING



O.D. outside diameter | I.D. inside diameter | R minimum bend radius to the centreline. Nominal, in inches.

Features

- Listed under the Underwriter's Laboratories
- CSA Certified by Canadian Standards Association
- 3/8 inch through 4 inch trade size

DOCUMENTS

Part page: <https://superflex.com/product/flexible-liquid-tight-conduit-3-4-700-ft-8432-r-700/>

Sealproof catalog, Rev. 2026 (PDF): <https://superflex.com/wp-content/uploads/2026/09/Sealproof-Weatherproof-Catalog-Rev-2026.pdf>