

Superflex Ltd. Pool & Spa Hose





For use on Spas, Hot Tubs and Swimmimg Pools. Above and below ground installations.



- In compliance with IAPMO® PS 33-90
- IAPMO[®] listed file No. SP-3342
- FDA Non-toxic formulation in complance with IAPMO® TSC 31-90
- Use with listed PVC solvent cements and primers

Unmatched Quality & Flexibility

- Manufactured from high quality virgin PVC compound
- Flexible PVC wall and cover for ease of use
- Rigid PVC spiral resists crushing and impact
- Flexible for easy handling and installation
- Outside diameter tolerance +.020"
- Temperature range -10 to 150°F.
- · Attractive off-white color

Less fitting required compared with PVC pipe

Part No.	S-012	S-034	S-100	S-114	S-112	S-200
Trade Size in inches	1/2	3/4	1	1-1/4	1-1/2	2
O.D. in inches	0.840	1.050	1.315	1.660	1.900	2.375
Bend Radius in inches	2	2	2	4	5	6
Working PSI at 70°F	100	100	100	80	70	60
Vacuum Rating at 70°F in/Hg	28	28	28	28	28	28
Approx. Lb/Ft	.15	.20	.27_	.34	.44	.66
Standard Length Ft.	100	100	100	100	50 &100	50

Superflex Ltd.

Manufacturer of P.V.C. Flexible Reinforced Hoses

Tel: 718-768-1400 Fax: 718-768-5065 400 S Second St. Elizabeth NJ 70206 www.superflex.com

