



For Custom Orders :

- a. Available in Black
 - b. Custom cut lengths available.
- Consult factory for details

PART NUMBER & DESCRIPTION			OD	ID
8430	3/8"	LFNC-B	.690 - .710 "	.484 - .504 "
8431	1/2"	LFNC-B	.820 - .840 "	.622 - .642 "
8432	3/4"	LFNC-B	1.030 - 1.050 "	.820 - .840 "
8433	1"	LFNC-B	1.290 - 1.315 "	1.041 - 1.066 "
8434	1-1/4"	LFNC-B	1.630 - 1.660 "	1.380 - 1.410 "
8435	1-1/2"	LFNC-B	1.865 - 1.900 "	1.575 - 1.600 "
8436	2"	LFNC-B	2.340 - 2.375 "	2.020 - 2.045 "
8437	2-1/2"	LFNC-B	2.840 - 2.875 "	2.480 - 2.555 "
8438	3"	LFNC-B	3.460 - 3.500 "	3.070 - 3.150 "
8439	3-1/2"	LFNC-B	3.960 - 4.000 "	3.500 - 3.590 "
8440	4"	LFNC-B	4.460 - 4.500 "	4.000 - 4.090 "

PRODUCT INFO:

Listed under the Underwriter's Laboratories

CSA Certified by Canadian Standards Association

3/8 inch to 4 inch trade size

Use with SEALPROOF® straight or right angle connectors

May also be used with metallic connectors for liquid-tight conduit

Resists corrosion, abrasion, oil, water, acid, metal shavings, and rough environments

Smooth inside for easier wire pulling, no hazardous sharp edges or burrs, will not damage conductors

COLOR: NA

Outdoor, sunlight resistant, direct burial

CSA rating - 18°C to 75°C

Light weight and lower installed cost

Quick installation, cuts with utility knife or PVC cutter

Integral rigid & flexible PVC construction

Resists abuse, pull and crushing

UL Rating: 80°C dry, 60°C wet. 70°C oil resistant

MATERIAL:	PVC	 Superflex Ltd. PROPERTY OF SUPERFLEX LTD SUPERFLEX LTD ELIZABETH, NJ	DESCRIPTION:	PART NO	REV DATE
CERTIFICATIONS:	UL 1660		SPECIFICATION SHEET FOR		
MARKING:	UL & CSA		SEALPROOF		
CERT#	E129973		Liquid Tight Conduit Type B		
	LL-84705		3/8" - 4" size		
	UL94-V0			REV: 1	11/27/2014

