

POOL AND SPA HOSE

FOR HOT TUBS AND SWIMMING POOLS



For use with Spa, Hot Tubs and Swimming Pools Above and below ground installations

- IAPMO listed file No. SP-3342
- FDA non-toxic formulation in compliance with IAPMO TSC 31-90
- For use with PVC Schedule 40 type fittings
- Use with Listed PVC solvent cements and primers
- Manufactured from high quality virgin PVC compound
- Phthalate Free
- Less fittings required compared with PVC pipe
- Flexible PVC wall and cover for ease of use
- Outside diameter tolerance +.020 inch
- Rigid PVC spiral resists crushing and impact
- Temperature range -10 to 150°F
- Flexible for easy handling and installation
- PSI and vac rating are based on an open ended system at ambient temperatures
- Attractive off-white color

ITEM#	SIZE	O.D.	BEND RADIUS	WORKING PSI AT 70°F	MIN BURST PRESSURE AT 70°F	MIN BURST PRESSURE AT 140°F	VAC RATING AT 70°F	APPROX WEIGHT
S-012	1/2 "	0.840 "	2 "	100	355	180	28 in/Hg	15 lb
S-034	3/4 "	1.050 "	2 "	100	355	180	28 in/Hg	20 lb
S-100	1 "	1.315 "	2 "	100	355	180	28 in/Hg	27 lb
S-114	1-1/4 "	1.660 "	4 "	80	250	125	28 in/Hg	34 lb
S-112	1-1/2 "	1.900 "	5 "	65	200	100	28 in/Hg	44 lb
S-200	2 "	2.375 "	6 "	60	175	90	28 in/Hg	66 lb
S-300	3 "	3.500 "	12 "	50	75	65	28 in/Hg	128 lb